



**DEPARTMENT OF PUBLIC WORKS
SIDEWALK, CURB AND APRON
PERMIT APPLICATION**

SIDEWALK	
Permit Number	
Permit Issue Date	
Permit Expiration Date	

PERMIT APPLICATION FOR SIDEWALK, CURB, APRON REPAIR OR REPLACEMENT

Project Information:		Incomplete applications will not be accepted	
Location Address:			
Section:	Block:	Lot:	
Type of Work:			
<input type="checkbox"/> Sidewalk:	Length: _____	Width: _____	Thickness: _____
<input type="checkbox"/> Curb:	Street Location: _____		Length: _____
<input type="checkbox"/> Apron:	Street Location: _____		Width: _____ (Note: Aprons permitted to be 12' wide maximum)
Contractor/Applicant Information:			
Name:			
Company Name:		Floral Park License Number:	<input type="checkbox"/> VFP Verified
Company Address:		City:	State: Zip:
Phone Number:		Email:	
Village Code Requirements Summary: <i>see Village Code section 81 for full regulations</i>			
<ol style="list-style-type: none"> All sidewalks, curbs and aprons shall be constructed of poured concrete, 3500 psi minimum, air entrained mix. The contractor shall provide a copy of the batch ticket for all ready-mixed concrete to the Village for record. When a site-mixed concrete is used, the contractor shall follow the Village specifications as outlined in Chapter 81 of the Village Code. The width of all sidewalks shall be a minimum of 4'-0" (unless otherwise approved by the Superintendent of Public Works) and shall be a minimum of 4" thick, except where such sidewalks are crossed by driveways; the sidewalks shall be a minimum of 6" thick through the width of such driveway. All aprons shall be a minimum of 6" thick and poured separate from the curb. Curb construction shall be constructed with a minimum width of 6" across at the top, 8" at the base. The height of the curb shall be 6" above grade and shall be a minimum depth of 12" below grade. The contractor must call before you dig - dial 811 a minimum of 48 hours before beginning any digging project. Village tree and root systems must not be disturbed. Once all work is formed, the contractor must schedule an inspection with the Village a minimum of 24-hour notice. An inspection to verify the size, depth, and reinforcement is required before any pour. All concrete work must be approved by the Village. 			
Applicant Statement & Signature:			
The undersigned affirms that I am the authorized agent for the property described herein, situated, lying and being within the Incorporated Village of Floral Park; that I have read and understand all items as here in stated, recognize that I am responsible for all activities occurring on the property, and that failure to comply with any of the items, notwithstanding any other items defined in the Village Code, may result in the temporary suspension or permanent revocation of the permits issued for construction on the premises in accordance with the Village Code.			
Print Name:		Signature:	Date:
Notary:			
On this _____ day of _____, 20____, before me personally came _____, to me known and known to me to be the person described in as the applicant and who executed the foregoing instrument and has acknowledged to me that he/she executed the same.			
		_____ Notary Public	
DPW Use Only:			
<input type="checkbox"/> Permit Fee: \$75	Receipt:	<input type="checkbox"/> Other:	
Permit Review	<input type="checkbox"/> Approval <input type="checkbox"/> Denial	Date:	By:
Inspection	<input type="checkbox"/> Approval <input type="checkbox"/> Denial	Date:	By: